



MATEBOX

For the new X-ESS G4, we get rid of the complicated wiring work by laying all the wires in the Matebox. All you need to do is just to install one module on the top of another, and connect all the cables which are already well-sorted in the Matebox in different ports.

PV	
Max. input voltage [Vdc]	600
Max. short circuit current [A]	16/16
No. of MPP trackers	2
BATTERY	
Battery voltage range [V]	80-480
Max. charge/discharge current [A]	30
ON-GRID	
Rated voltage [Vac], frequency [Hz]	220/230/240, 50/60
Max. apparent on-grid input/output power [VA]	7500
Max. on-grid current [A]	32.6
OFF-GRID	
Rated voltage [Vac], frequency [Hz]	230, 50/60
Rated power [VA]	7500
Rated current [A]	32.6
GRID	
Rated grid voltage [Vac], frequency [Hz]	220/230/240, 50/60
Max. input current [A]	60
LOAD	
Rated voltage [Vac], frequency [Hz]	220/230/240, 50/60
Max. current [A]	60
ENVIRONMENT LIMIT	
IP class	IP54
Protection class	Class I
Operating temperature range [°C]	-35... +60°C (derating at +45°C)
Storage temperature [°C]	-40... +70°C
Humidity [%]	0-100 (condensing)
Altitude [m]	<3000
Over voltage category	III(AC), III(DC)
OTHER	
Cooling concept	Natural
DIMENSION AND WEIGHT	
Dimensions [mm]	482*437*185
Net weight [kg]	10

X1-MATEBOX



X3-MATEBOX BASIC



PV	
Max. input voltage[Vdc]	1000
Max. short circuit current[A]	30/16
No. of MPP trackers	2
BATTERY	
Battery voltage range[V]	180-650
Max.charge/discharge current[A]	30
ON-GRID	
Rated voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. apparent Grid(INV) input/output power[VA]	20000/20000
Max. Grid(INV) input/output current[A]	32/32
OFF-GRID	
Rated voltage[Vac], frequency[Hz]	400, 50/60
Max. power[VA]	15000
Max. current	24.1
GRID	
Rated grid voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. input/output current[A]	32/32
LOAD	
Rated voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. current[A]	24.1
ENVIRONMENT LIMIT	
IP class	IP54
Protection class	Class I
Operating temperature range[°C]	-25~+60°C (derating at +45°C)
Storage temperature[°C]	-40~+70°C
Humidity[%]	0-100 (condensing)
Altitude[m]	<3000
Over voltage category	III(AC), III(DC)
OTHER	
Cooling concept	Natural
DIMENSION AND WEIGHT	
Dimensions[mm]	533*397*204
Net weight[kg]	7.5

X3-MATEBOX ADVANCED



PV	
Max. input voltage[Vdc]	1000
Max. short circuit current[A]	30/16
No. of MPP trackers	2
BATTERY	
Battery voltage range[V]	180-650
Max.charge/discharge current[A]	30
ON-GRID	
Rated voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. apparent Grid(INV) input/output power[VA]	15000/15000
Max. Grid(INV) input/output current[A]	24.1/24.1
OFF-GRID	
Rated voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. power[VA]	15000
Max. current	24.1
GRID	
Rated grid voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. input/output current[A]	63/24.1
LOAD	
Rated voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. current[A]	63
ENVIRONMENT LIMIT	
IP class	IP54
Protection class	Class I
Operating temperature range[°C]	-25~+60°C (derating at +45°C)
Storage temperature[°C]	-40~+70°C
Humidity[%]	0-100 (condensing)
Altitude[m]	<3000
Over voltage category	III(AC), III(DC)
OTHER	
Cooling concept	Natural
DIMENSION AND WEIGHT	
Dimensions[mm]	551*512*204
Net weight[kg]	14.5